

## 1 **A Appendix**

### 2 **A.1 General Information**

#### 3 **A.1.1 Links**

4 The FlexMol code is available at our public repository: [https://github.com/Steven51516/](https://github.com/Steven51516/FlexMol)  
5 [FlexMol](https://github.com/Steven51516/FlexMol). The code to reproduce the experiments described in this paper can be found in the  
6 experiments directory of the repository. The FlexMol experiment split used in our experiment are  
7 adapted from MolTrans: <https://github.com/kexinhuang12345/MolTrans>.

#### 8 **A.1.2 Licenses**

9 FlexMol is under the BSD 3-Clause License. We, the authors, bear all responsibility in case of  
10 violation of rights.

### 11 **A.2 Drug Encoders Implemented in FlexMol**

#### 12 **A.2.1 Sequence and Fingerprint-based Encoders**

13 **Morgan**: Generates a 1024-length bit vector encoding circular radius-2 substructures, processed with  
14 an MLP. [28]

15 **Daylight**: Produces a 2048-length vector encoding path-based substructures, processed with an MLP.  
16 [28]

17 **ErG**: Creates a 315-dimensional 2D pharmacophore description for scaffold hopping, processed with  
18 an MLP. [32]

19 **PubChem**: Generates an 881-length bit vector where each bit corresponds to a significant substructure,  
20 processed using an MLP. [16]

21 **ChemBERTa**: Generates embeddings from SMILES strings using the pretrained ChemBERTa model,  
22 processed with a linear layer or MLP. [23]

23 **ESPF**: Produces a 2586-length sub-structure partition vector, processed with an MLP. [14]

24 **CNN**: One-hot encodes SMILES strings and processes them through a multi-layer 1D convolutional  
25 neural network, followed by a global max pooling layer. [14]

26 **Transformer**: Generates sub-structure partition fingerprints from SMILES strings and encodes them  
27 using a self-attention-based transformer model. [14]

#### 28 **A.2.2 2D Graph-based Encoders**

29 Preprocessing involves creating 2D molecular graphs from SMILES strings using RDKit. These  
30 graphs are then encoded using various graph neural network models implemented with DGL:

31 **GCN, GAT, GIN**: Standard graph neural networks to capture relational and topological features in  
32 2D drug graphs. [17, 34, 37]

33 **AttentiveFP**: Utilizes attention mechanisms to prioritize significant molecular substructures. [36]

34 **NeuralFP**: Employs neural fingerprinting methods to capture detailed molecular features. [8]

35 **MPNN**: Uses message-passing neural networks to transmit information among atoms and bonds in  
36 the graph.[10]

#### 37 **A.2.3 3D Graph-based Encoders**

38 Preprocessing involves creating 3D molecular graphs from SMILES strings using RDKit, considering  
39 spatial conformation. These graphs are then encoded using:

40 **SchNet**: SchNet models to capture 3D spatial relationships. [29]

41 **MGCN**: Multi-level graph convolutional networks to learn spatial features. [20]

### 42 **A.3 Protein Encoders Implemented in FlexMol**

#### 43 **A.3.1 Sequence-based Encoders**

44 **CNN**: One-hot encodes the amino acid sequences and processes them through a multi-layer 1D  
45 convolutional neural network, followed by a global max pooling layer. [14]

46 **Transformer**: Generates sub-structure partition fingerprints from amino acid sequences and encodes  
47 them using a self-attention-based transformer model. [14]

48 **AAC**: Generates an 8,420-length vector representing amino acid k-mers, processed with an MLP.  
49 [26]

50 **ESPF**: Produces a 4,114-length sub-structure partition vector, processed with an MLP. [14]

51 **PseudoAAC**: Generates a 30-length vector considering protein hydrophobicity and hydrophilicity  
52 patterns, processed with an MLP. [4]

53 **Quasi-seq**: Generates a 100-length quasi-sequence order descriptor using sequence-order-coupling  
54 numbers, processed with an MLP. [3]

55 **Conjoint triad**: Produces a 343-length vector based on the frequency distribution of three continuous  
56 amino acids, processed with an MLP. [30]

57 **Auto correlation**: Generates a 720-length vector based on the autocorrelation of physicochemical  
58 properties along the sequence, processed with an MLP. [12]

59 **CTD**: Produces a 147-length vector by calculating composition, transition, and distribution descrip-  
60 tors, processed with an MLP. [7]

61 **ESM**: Directly generates embeddings using a pretrained ESM model, processed with a linear layer or  
62 MLP. [27]

63 **ProtTrans-t5, ProtTrans-bert, ProtTrans-albert**: Directly generates embeddings using pretrained  
64 models (T5, BERT, ALBERT respectively), processed with a linear layer or MLP. [9]

#### 65 **A.3.2 3D Graph-based Encoders**

66 Preprocessing involves creating 3D graphs from protein PDB structures. These graphs are then  
67 encoded using various graph neural network models:

68 **GCN, GAT, GIN**: Standard graph neural networks to capture spatial features in 3D protein structures.  
69 [17, 34, 37]

70 **GCN\_ESM, GAT\_ESM, GIN\_ESM**: Combines standard GNNs with additional ESM features for  
71 enhanced node representations. [35]

72 **PocketDC**: Identifies and constructs graphs from binding pockets using DeepChem, encoded with  
73 GCN. [39]

74 **GVP**: Utilizes Geometric Vector Perceptrons (GVP) to capture geometric and vectorial features. [15]

75 **GearNet**: Employs pretrained GearNet layers with relational message passing to capture geometric  
76 properties and spatial features. [40]

### 77 **A.4 Interaction Layers Implemented in FlexMol**

78 **Bilinear Attention**: The Bilinear Attention Network (BAN) layer captures interactions between  
79 2D feature sets by computing bilinear transformations, followed by attention pooling and batch  
80 normalization. [1]

81 **Bilinear Fusion:** Combines 1D features from two sources using a bilinear transformation and ReLU  
82 activation, capturing multiplicative interactions for enhanced feature representation. [19]

83 **Bidirectional Cross Attention:** Combines 2D embeddings from two sources using bidirectional  
84 attention and max pooling, creating a unified representation. [25]

85 **Highway:** Combines 1D features using multiple highway layers with gated mechanisms to regulate  
86 information flow. [41]

87 **Gated Fusion:** Combines 1D features from two sources using gated mechanisms and transformations,  
88 producing a fused representation. [22]

89 **Multi-Head Attention:** Applies attention mechanisms to 2D features using multiple heads, with  
90 optional residual connections and layer normalization. [33]

91 **Concatenation:** Concatenation is the simplest form of combining multiple feature embeddings by  
92 joining them end-to-end.

### 93 A.5 Example Usage of FlexMol

94 This section provides a simple example to using FlexMol for drug-target interaction prediction. A  
95 more detailed set of tutorials can be found in the tutorials directory of our repository.




Figure 1: The example model constructed using FlexMol involves several stages. First, drug and protein sequences/structures are encoded using selected encoders: GCN for drug encoding, PocketDC for protein structure encoding, and AAC for protein sequence encoding. These encoded features are then stacked and passed through a self-attention interaction layer to capture complex relationships. The output of the interaction layer is flattened and processed through a Multi-Layer Perceptron (MLP) with specified hidden layers.

#### 96 A.5.1 Loading the Dataset

97 First, we import the necessary modules from FlexMol and load the DAVIS dataset.

```
98 # Import necessary modules from FlexMol
99 from FlexMol.dataset.loader import load_DTI
100 from FlexMol.encoder import FlexMol
101 from FlexMol.task import BinaryTrainer
102
103
104 # Load the DAVIS dataset from the specified directory
105 dir = "data/DAVIS/"
106 train_df = load_DTI(dir + "train.txt")
107 val_df = load_DTI(dir + "val.txt")
```

```
100 test_df = load_DTI(dir + "test.txt")
```

110 The `load_DTI` function is a general-purpose utility that loads drug-target interaction data from the specified directory into DataFrames for training, validation, and testing. The loaded DataFrame contains four columns: drug sequence, protein sequence, protein PDB ID, and interaction label.

### 113 A.5.2 Initializing Encoders

114 Next, we initialize the drug and protein encoders.

```
115 # Initialize drug and protein encoders
116 # Graph Convolutional Network for drug encoding
117 # PocketDC encoder for protein structures
118 # Amino Acid Composition encoder for protein sequences
119 FM = FlexMol()
120 de = FM.init_drug_encoder("GCN")
121 pe1 = FM.init_prot_encoder("PocketDC", pdb=True, pocket_num=3)
122 pe2 = FM.init_prot_encoder("AAC")
```

125 Here, we use a Graph Convolutional Network (GCN) for drug encoding, PocketDC for protein structure encoding, and Amino Acid Composition (AAC) for protein sequence encoding.

### 127 A.5.3 Stacking Features and Setting Interaction Layers

128 We then stack the features from the different encoders and set the interaction layer to self-attention.

```
129 # Stack the features from different encoders
130 # Set interaction layer to self-attention
131 # Flatten the attention outputs for MLP input
132 # Apply a Multi-Layer Perceptron (MLP) with specified hidden layers
133 features_stack = FM.stack([de, pe1, pe2])
134 attention = FM.set_interaction(features_stack, "self-attention")
135 features_flatten = FM.flatten(attention)
136 output = FM.apply_mlp(features_flatten, hidden_layers=[512, 512, 256], head=1)
```

140 The `stack` method combines the outputs of the encoders, and the `set_interaction` method applies a self-attention mechanism to these combined features. The `flatten` method prepares the attention layer outputs for the MLP, and the `apply_mlp` method sets up the MLP with specified hidden layers.

### 143 A.5.4 Building and Training the Model

144 Finally, we initialize the `BinaryTrainer` and train/test the model.

```
145 # Build the FlexMol model
146 # Initialize the BinaryTrainer for training the model
147 FM.build_model()
148 trainer = BinaryTrainer(
149     FM, early_stopping="roc_auc", test_metrics=["roc_auc", "pr_auc"],
150     device="cuda:0", epochs=50, patience=10, lr=0.0001, batch_size=64,
151     metrics_dir = "metrics/example_run"
152 )
```

155 The `BinaryTrainer` is configured for training binary classification tasks with early stopping based on the ROC-AUC metric and evaluates the model using both ROC-AUC and PR-AUC metrics. After testing, the metrics are saved to the user-specified directory.

158 The code provided in this section serves as a practical example of how FlexMol can be utilized for molecular relational learning tasks, showcasing its flexibility and ease of use.

## 160 A.6 Additional Experiments for DDI

### 161 A.6.1 Experiment Setup

162 **Dataset:** We used DrugBank, downloaded using the TDC Python library [13], for the evaluation  
163 of FlexMol-baselines. DrugBank contains 191,808 DDI tuples with 1,706 drugs. Each drug is  
164 represented in SMILES format, from which molecular graphical representations are generated using  
165 the Python library RDKit. There are 86 interaction types describing how one drug affects the  
166 metabolism of another. Each DDI pair is considered a positive sample, from which a negative sample  
167 was generated using the method described in the GMPNN-CS framework [24].

168 **Evaluation Method:** We performed a stratified split of the dataset to maintain the same interaction  
169 type proportions in the training (60%), validation (20%), and test (20%) sets. This was repeated three  
170 times, resulting in three stratified randomized folds.

171 We constructed six FlexMol baselines as detailed in Table 1. The models were trained in mini-  
172 batches of 512 with a learning rate of 0.0001. Five state-of-the-art(SOTA) methods were selected  
173 for comparison: MHCADDI [6], GMPNN-CS [24], GAT-DDI [24], GMPNN-U [24], and MR-GNN  
174 [38].

Table 1: FlexMol Experimental Settings on the DrugBank dataset

Experiment No.	Drug Encoder 1	Drug Encoder 2	Interaction	Input Feature
1	CNN	CNN	-	$d_s$
2	CNN	GCN	-	$d_s + d_g$
3	CNN+PubChem	GCN+PubChem	-	$d_s + d_g$
4	PubChem	PubChem	-	$d_s$
5	Transformer	Transformer	-	$d_s$
6	Transformer	Transformer	Cross Attention	$d_s$

**Note:**  $d_s$  = drug sequence,  $d_g$  = drug graph, '-' denotes concatenation for combining embeddings.

### 175 A.6.2 DDI Experiment Results

Table 2: Comparison of Model Performance on the DrugBank dataset.

Experiment No. / Method	Accuracy	ROC-AUC	PR-AUC	Precision	Recall
MR-GNN	96.04 ± 0.05	98.87 ± 0.04	<b>98.57 ± 0.06</b>	94.48 ± 0.08	<b>97.78 ± 0.03</b>
MHCADDI	83.80 ± 0.27	91.16 ± 0.31	89.26 ± 0.37	78.90 ± 0.06	92.26 ± 0.63
SSI-DDI	<b>96.33 ± 0.09</b>	<b>98.95 ± 0.08</b>	98.57 ± 0.14	<b>95.09 ± 0.08</b>	97.70 ± 0.14
GAT-DDI	89.81 ± 1.00	95.21 ± 0.70	93.56 ± 0.90	87.04 ± 1.11	93.56 ± 0.52
GMPNN-CS	95.30 ± 0.05	98.46 ± 0.01	97.94 ± 0.02	93.60 ± 0.07	97.22 ± 0.1
1	83.39 ± 0.08	90.01 ± 0.10	86.35 ± 0.13	81.40 ± 0.10	86.20 ± 0.06
2	80.42 ± 0.20	87.70 ± 0.60	83.92 ± 1.52	78.22 ± 2.20	84.41 ± 0.94
3	83.40 ± 0.26	89.68 ± 0.10	85.73 ± 0.20	80.83 ± 0.06	85.60 ± 0.47
4	82.12 ± 0.15	89.20 ± 0.30	85.54 ± 0.44	80.67 ± 0.30	84.57 ± 0.40
5	87.03 ± 0.19	92.33 ± 0.12	89.13 ± 0.16	83.42 ± 0.10	92.34 ± 0.35
6	87.27 ± 0.24	92.49 ± 0.09	89.37 ± 0.12	83.71 ± 0.20	92.92 ± 0.83

176 Table 2 shows that while simple combinations using FlexMol generally perform slightly lower than  
177 SOTA methods, they remain closely competitive. Experiment #2, in particular, demonstrates that  
178 using different encoders for the two drugs tends to decrease performance. Additionally, the interaction  
179 layers added in experiment #6 improve model performance compared to experiment #5, highlighting  
180 the importance of interaction layers in enhancing the predictive capabilities of the model.

181 **A.7 Additional Experiments for PPI**

182 **A.7.1 Experiment Setup**

183 **Dataset:** We used the Guo yeast dataset [11], which includes 11,188 PPI pairs, with 5,594  
 184 positive and 5,594 negative interactions. The data was collected from the Saccharomyces  
 185 cerevisiae core subset of the Database of Interacting Proteins (DIP), version DIP\_20070219.  
 186 The dataset is available at [https://github.com/aidantee/xCAPT5/tree/master/data/  
 187 Golden-standard-datasets/Guo-2008](https://github.com/aidantee/xCAPT5/tree/master/data/Golden-standard-datasets/Guo-2008)

188 **Evaluation Method:** We tested using 5-fold cross-validation with a random split following the  
 189 xCAPT5 framework [5].

190 We constructed six FlexMol baselines as detailed in Table 3. The models were trained in mini-  
 191 batches of 128 with a learning rate of 0.001. Five state-of-the-art(SOTA) methods were selected for  
 192 comparison: PIPR [2], FSNN-LGBM [21], MARPPI [18], TAGPPI[31], and xCAPT5[5].

Table 3: FlexMol Experimental Settings on the Guo dataset

Experiment No.	Protein Encoder 1	Protein Encoder 2	Interaction	Input Feature
1	CNN	CNN	-	$p_s$
2	CNN	GCN	-	$p_s + p_g$
3	AAC	AAC	-	$p_s$
4	AAC+CNN	AAC+GCN	-	$p_s + p_g$
5	Transformer	Transformer	-	$p_s$
6	Transformer	Transformer	Cross Attention	$p_s$

**Note:**  $p_s$  = protein sequence,  $p_g$  = protein graph, '-' denotes concatenation for combining embeddings.

193 **A.7.2 PPI Experiment Results**

Table 4: Comparison of Model Performance on the Guo dataset.

Experiment No. / Method	Accuracy	Precision	Recall	F1-Score
PIPR	96.47 ± 0.21	96.31 ± 0.23	96.67 ± 0.22	96.48 ± 0.20
FSNN-LGBM	98.46 ± 0.20	98.73 ± 0.25	98.18 ± 0.18	98.45 ± 0.20
MARPPI	96.03 ± 0.76	98.12 ± 0.98	93.51 ± 1.22	NA
TAGPPI	97.81	98.10	98.26	97.80
HNSPPI	98.57 ± 0.11	98.30 ± 0.22	98.85 ± 0.13	98.57 ± 0.11
xCAPT5	<b>99.76 ± 0.05</b>	<b>99.76 ± 0.04</b>	<b>99.75 ± 0.07</b>	<b>99.37 ± 0.27</b>
1	77.07 ± 0.87	85.52 ± 0.69	66.81 ± 2.43	71.81 ± 1.59
2	88.12 ± 1.93	89.61 ± 0.64	86.32 ± 4.47	87.91 ± 2.53
3	89.71 ± 2.04	89.31 ± 1.32	86.34 ± 0.34	89.72 ± 2.25
4	90.02 ± 1.52	91.96 ± 1.80	87.92 ± 4.83	89.73 ± 2.22
5	90.26 ± 0.23	90.24 ± 2.25	90.42 ± 2.32	90.31 ± 1.03
6	89.18 ± 1.09	90.22 ± 2.28	89.10 ± 0.93	89.51 ± 1.02

**Note:** NA indicates that data is not available in the reference literature. The TAGPPI method does not include standard deviation values in the literature, and thus no standard deviations are reported here.

194 From table 4, we observed that all results from FlexMol baselines are significantly lower than SOTA  
 195 methods. This suggests that the PPI task is more challenging and requires more specialized modeling  
 196 methods rather than simple encoder combinations. However, some trends were noted. For instance,  
 197 the combination of encoders in Experiment #4 improves performance compared to Experiments

198 #2 and #3. Interestingly, we found that the cross-attention in Experiment #6 does not improve  
199 performance, indicating that the influence of interaction layers can vary depending on the specific  
200 dataset and task.

## 201 References

- 202 [1] Peizhen Bai, Filip Miljković, Bino John, and Haiping Lu. Interpretable bilinear attention  
203 network with domain adaptation improves drug–target prediction. *Nature Machine Intelligence*,  
204 5(2):126–136, Feb 2023.
- 205 [2] Minghao Chen, Chien Ju-Ting Ju, Guangyu Zhou, Xinkai Chen, Ting Zhang, Kai-Wei Chang,  
206 Carlo Zaniolo, and Wei Wang. Multifaceted protein-protein interaction prediction based on  
207 siamese residual rnn. *Bioinformatics*, 35(14):305–314, 2019.
- 208 [3] Kuo-Chen Chou. Prediction of protein subcellular locations by incorporating quasi-sequence-  
209 order effect. *Biochemical and Biophysical Research Communications*, 278(2):477–483, Nov  
210 2000.
- 211 [4] Kuo-Chen Chou. Prediction of protein cellular attributes using pseudo-amino acid composition.  
212 *Proteins: Structure, Function, and Bioinformatics*, 43(3):246–255, Mar 2001.
- 213 [5] Thanh Hai Dang and Tien Anh Vu. Xcapt5: Protein–protein interaction prediction using deep  
214 and wide multi-kernel pooling convolutional neural networks with protein language model.  
215 *BMC Bioinformatics*, 25(1), Mar 2024.
- 216 [6] Andreea Deac, Yu-Hsiang Huang, Petar Veličković, et al. Drug-drug adverse effect prediction  
217 with graph co-attention. In *ICML Workshop on Computational Biology*. ICLR, May 2019.
- 218 [7] I Dubchak, I Muchnik, S R Holbrook, and S H Kim. Prediction of protein folding class using  
219 global description of amino acid sequence. *Proceedings of the National Academy of Sciences*,  
220 92(19):8700–8704, Sep 1995.
- 221 [8] David Duvenaud, Dougal Maclaurin, Jorge Aguilera-Iparraguirre, Rafael Gómez-Bombarelli,  
222 Timothy Hirzel, Alán Aspuru-Guzik, and Ryan P Adams. Convolutional networks on graphs  
223 for learning molecular fingerprints. *arXiv preprint arXiv:1509.09292*, 2015.
- 224 [9] Ahmed Elnaggar, Michael Heinzinger, Christian Dallago, Ghalia Rehawi, Wang Yu, Llion Jones,  
225 Tom Gibbs, Tamas Feher, Christoph Angerer, Martin Steinegger, Debsindhu Bhowmik, and  
226 Burkhard Rost. Prottrans: Towards cracking the language of lifes code through self-supervised  
227 deep learning and high performance computing. *IEEE Transactions on Pattern Analysis and*  
228 *Machine Intelligence*, pages 1–1, 2021.
- 229 [10] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural  
230 message passing for quantum chemistry. *arXiv preprint arXiv:1704.01212*, 2017.
- 231 [11] Yanzhi Guo, Lezheng Yu, Zhining Wen, and Menglong Li. Using support vector machine  
232 combined with auto covariance to predict protein–protein interactions from protein sequences.  
233 *Nucleic Acids Research*, 36(9):3025–3030, Apr 2008.
- 234 [12] David S. Horne. Prediction of protein helix content from an autocorrelation analysis of sequence  
235 hydrophobicities. *Biopolymers*, 27(3):451–477, Mar 1988.
- 236 [13] Kexin Huang, Tianfan Fu, Wenhao Gao, Yue Zhao, Yusuf Roohani, Jure Leskovec, Connor W.  
237 Coley, Cao Xiao, Jimeng Sun, and Marinka Zitnik. Therapeutics data commons: Machine  
238 learning datasets and tasks for drug discovery and development. *Advances in Neural Information*  
239 *Processing Systems*, 2 2021.
- 240 [14] Kexin Huang, Tianfan Fu, Lucas M Glass, Marinka Zitnik, Cao Xiao, and Jimeng Sun.  
241 Deepurpose: A deep learning library for drug–target interaction prediction. *Bioinformat-*  
242 *ics*, 36(22–23):5545–5547, Dec 2020.
- 243 [15] Bowen Jing, Stephan Eismann, Patricia Suriana, Raphael John Lamarre Townshend, and Ron  
244 Dror. Learning from protein structure with geometric vector perceptrons. In *International*  
245 *Conference on Learning Representations*, 2021.

- 246 [16] Sunghwan Kim, Jian Chen, Tiezheng Cheng, Asta Gindulyte, Jane He, Sherry He, Qingliang Li,  
247 Benjamin A Shoemaker, Paul A Thiessen, Bin Yu, Leonid Zaslavsky, Jie Zhang, and Evan E  
248 Bolton. Pubchem 2019 update: improved access to chemical data. *Nucleic Acids Research*,  
249 47(D1):D1102–D1109, 2019.
- 250 [17] Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional  
251 networks. In *Proceedings of the International Conference on Learning Representations (ICLR)*,  
252 2017.
- 253 [18] Xiaoyan Li, Peng Han, Weiliang Chen, Changxin Gao, Shuai-peng Wang, Ting Song, Meiyu Niu,  
254 and Alejandro Rodriguez-Patón. Marppi: boosting prediction of protein–protein interactions  
255 with multi-scale architecture residual network. *Briefings in Bioinformatics*, 24(1):524, 2023.
- 256 [19] Tsung-Yu Lin, Aruni RoyChowdhury, and Subhransu Maji. Bilinear cnn models for fine-grained  
257 visual recognition. In *Proceedings of the IEEE international conference on computer vision*,  
258 pages 1449–1457, 2015.
- 259 [20] Chengqiang Lu, Qi Liu, Chao Wang, Zhenya Huang, Peize Lin, and Lixin He. Molecular  
260 property prediction: A multilevel quantum interactions modeling perspective. *Proceedings of  
261 the AAAI Conference on Artificial Intelligence*, 33(01):1052–1060, Jul 2019.
- 262 [21] Saurav Mahapatra and Satyabrata S Sahu. Improved prediction of protein–protein interaction  
263 using a hybrid of functional-link siamese neural network and gradient boosting machines.  
264 *Briefings in Bioinformatics*, 22(6):255, 2021.
- 265 [22] Qi Mao, Hanxiao Wang, Roger W. H. Lau, Peter K. K. Loh, and Xiaorong Li. Gated multimodal  
266 units for information fusion. In *Proceedings of the Twenty-Sixth International Joint Conference  
267 on Artificial Intelligence (IJCAI-17)*, pages 2314–2320, 2017.
- 268 [23] Sylwia Nowakowska. *Chemberta-2: Fine-tuning for molecule’s HIV replication inhibition  
269 prediction*, Sep 2023.
- 270 [24] Arnold K Nyamabo, Hui Yu, Zun Liu, and Jian-Yu Shi. Drug–drug interaction prediction with  
271 learnable size-adaptive molecular substructures. *Briefings in Bioinformatics*, 23(1), Oct 2021.
- 272 [25] Ying Qian, Xinyi Li, Jian Wu, and Qian Zhang. Mcl-dti: Using drug multimodal information  
273 and bi-directional cross-attention learning method for predicting drug–target interaction. *BMC  
274 Bioinformatics*, 24(1), Aug 2023.
- 275 [26] M. Reczko, D. Karras, and H. Bohr. An update of the def database of protein fold class  
276 predictions. *Nucleic Acids Research*, 25(1):235–235, Jan 1997.
- 277 [27] Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Jason Liu, Demi  
278 Guo, Myle Ott, C. Lawrence Zitnick, Jerry Ma, and Rob Fergus. Biological structure and  
279 function emerge from scaling unsupervised learning to 250 million protein sequences. *PNAS*,  
280 2019.
- 281 [28] David Rogers and Mathew Hahn. Extended-connectivity fingerprints. *Journal of Chemical  
282 Information and Modeling*, 50(5):742–754, 2010.
- 283 [29] Kristof T Schütt, Pieter-Jan Kindermans, Huziel E Saucedo, Stefan Chmiela, Alexandre  
284 Tkatchenko, and Klaus-Robert Müller. Schnet: A continuous-filter convolutional neural net-  
285 work for modeling quantum interactions. *Advances in Neural Information Processing Systems*,  
286 30:992–1002, 2017.
- 287 [30] Juwen Shen, Jian Zhang, Xiaomin Luo, Weiliang Zhu, Kunqian Yu, Kaixian Chen, Yixue Li, and  
288 Huanliang Jiang. Predicting protein-protein interactions based only on sequences information.  
289 *Proceedings of the National Academy of Sciences*, 104(11):4337–4341, 2007.
- 290 [31] Bo Song, Xiaoyong Luo, Xin Luo, Yong Liu, Zhibo Niu, and Xiangxiang Zeng. Learning  
291 spatial structures of proteins improves protein–protein interaction prediction. *Briefings in  
292 Bioinformatics*, 23(2):558, 2022.
- 293 [32] Nikolaus Stiefl, Ian A. Watson, Knut Baumann, and Andrea Zaliani. Erg: 2d pharmacophore  
294 descriptions for scaffold hopping. *ChemInform*, 37(17), Apr 2006.

- 295 [33] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez,  
296 Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information*  
297 *processing systems*, pages 5998–6008, 2017.
- 298 [34] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua  
299 Bengio. Graph attention networks. In *Proceedings of the International Conference on Learning*  
300 *Representations (ICLR)*, 2018.
- 301 [35] Fang Wu, Lirong Wu, Dragomir Radev, Jinbo Xu, and Stan Z. Li. Integration of pre-trained  
302 protein language models into geometric deep learning networks. *Communications Biology*, 6(1),  
303 Aug 2023.
- 304 [36] Zhaoping Xiong, Dingyan Wang, Xiaohong Liu, Feisheng Zhong, Xiaozhe Wan, Xutong Li,  
305 Zhaojun Li, Xiaomin Luo, Kaixian Chen, Hualiang Jiang, and et al. Pushing the boundaries of  
306 molecular representation for drug discovery with the graph attention mechanism. *Journal of*  
307 *Medicinal Chemistry*, 63(16):8749–8760, Aug 2019.
- 308 [37] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural  
309 networks? In *Proceedings of the International Conference on Learning Representations (ICLR)*,  
310 2019.
- 311 [38] Nuo Xu, Pinghui Wang, Long Chen, et al. Mr-gnn: Multi-resolution and dual graph neural  
312 network for predicting structured entity interactions. In *Proceedings of the 28th International*  
313 *Joint Conference on Artificial Intelligence (IJCAI)*, volume 2019-August, pages 3968–3974.  
314 International Joint Conferences on Artificial Intelligence Organization, 2019.
- 315 [39] Mehdi Yazdani-Jahromi, Niloofar Yousefi, Aida Tayebi, Elayaraja Kolanthai, Craig J Neal,  
316 Sudipta Seal, and Ozlem Ozmen Garibay. Attentionsitedti: An interpretable graph-based model  
317 for drug-target interaction prediction using nlp sentence-level relation classification. *Briefings*  
318 *in Bioinformatics*, 23(4), Jul 2022.
- 319 [40] Zuobai Zhang, Minghao Xu, Arian Jamasb, Vijil Chenthamarakshan, Aurelie Lozano, Payel  
320 Das, and Jian Tang. Protein representation learning by geometric structure pretraining. In  
321 *International Conference on Learning Representations*, 2023.
- 322 [41] Yan Zhu, Lingling Zhao, Naifeng Wen, Junjie Wang, and Chunyu Wang. Datadta: A multi-  
323 feature and dual-interaction aggregation framework for drug–target binding affinity prediction.  
324 *Bioinformatics*, 39(9), Sep 2023.